



9316DE

Model		DVR-9216DE	
System	Main processor	Dual-core embedded processor	
	Operation system	Embedded LINUX	
	Control	USB mouse, IR remote,Front panel,Network	
	Image splitter	1/4/9/16	
Video	Video standard	PAL(625Line,50f/s),NTSC(525Line,60f/s)	
	Video compression	H.264	
	Preview quality	D1:PAL(720*576);NTSC(720*480)	
	Playback quality	D1:PAL(720*576);NTSC(720*480)	
	Sync Playback	1~16ch D1(realtime)	
	Video Detection	Motion detection,MD Zones:396(22*18),Video Loss&Camera Blank	
Audio	Audio compression	G711A	
	Intercom	Support	
Record & Playback	Record modes	manual>alarm>motion>timing	
	Record rate	PAL:1~25fps;NTSC:1~30FPS	
	Video search	Time/Date,Alarm,Motion Detection,Log,event,channel	
Backup	Record storage	Local HDD,Network	
	Backup modes	Network,Flash disk,Movable HDD,Internal SATA burner	
Interface	Video input	16ch BNC	
	Audio input	16ch RCA	
	Video output	1 HDMI,1 VGA,1 BNC,1 Spot output	
	Audio output	1 RCA	
	Alarm		16ch input,3ch output
			Triger events:Recording,PTZ,Tour,Alarm,Video push,Email,FTP,Spot,Buzzer&Screen tips
	Network		RJ45 10M/100M self-adjusted Ethernet interface
			Remote surveillance,playback,configuration,PTZ control,backup,information search,support IE,CMS
	PTZ	1 RS485	
	USB	2 USB2.0	
	SATA	4HDD(or 7HDD+1CD/DVD RW)	
	E-SATA	Support	
	Loop-out	Support	
	DVD RW(Optional)	Support	
Mobile surveillance	Support	Iphone, Android,Symbian,Windows,Blackberry	
Environmental	Power supply	AC 110-240V,50/60Hz	
	Working	-10~+55℃/10~90%RH/86~106kpa	
	Dimmension	430(L)*480(W)*88(H)mm	