



# Gega Formix

Securité Physique & Système

**Adresse :** Hay Moulay Abdellah Bd Al Qods Rue 202 N°33 Ain Ch ok Bp 20153 Casablanca, MAROC.

**Tel:** 05 22 52 67 11 **Fax:** 05 22 52 67 12 **Website:** <http://www.sonycam.ma>

**E-mail:** [s.commercial@gegaformix.ma](mailto:s.commercial@gegaformix.ma) & [info@gegaformix.ma](mailto:info@gegaformix.ma)

## H.264 4CH DVRs

Ver.: 201101A

Model No.	Specification	Products Show
LS-9004H	<p>Video Input/Output: BNC 4CH In/ 1CH Out/ VGA 1CH Out</p> <p>Audio Input/Output: RCA 4CH In/ 1CH Out</p> <p>Alarm Input/Output: Alarm 4CH In/ 1CH Out</p> <p>Compression Method: H.264</p> <p>Real time recording support: CIF:352 240 with 240 Fps (NTSC); 352 288 with 200 Fps (PAL) D1:720 480 with 120 Fns (NTSC); 704 576 with 100 Fns (PAL )</p> <p>Preview resolution: 720 x 480 ( NTSC ), 704 x 576 ( PAL ) ; Playback resolution: D1 x 4</p> <p>Hexaplex operation simultaneously: Preview, recording, playback, and network live. backup. playback</p> <p>1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software</p> <p>Remote Control, PTZ, RS485 x 1, 2 USB, 1 IR Controller</p> <p>1 SATA Hard Disk interface Backup: USB2.0 and Network Support</p> <p>remote view by Mobilephone</p> <p>Dimensions (L W H): 280mm 229mm 43mm. weight: 3.0kg</p>	
LS-9004S	<p>Video Input/Output: BNC 4CH In/ 1CH Out/ VGA 1CH Out</p> <p>Audio Input/Output: RCA 4CH In/ 1CH Out</p> <p>Alarm Input/Output: Alarm 4CH In/ 1CH Out</p> <p>Compression Method: H.264</p> <p>Real time recording support: CIF:352 240 with 240 Fps (NTSC); 352 288 with 200 Fps (PAL) D1:720 480 with 120 Fns (NTSC); 704 576 with 100 Fns (PAL )</p> <p>Preview resolution: 720 x 480 ( NTSC ), 704 x 576 ( PAL ) ; Playback resolution: D1 x 4</p> <p>Hexaplex operation simultaneously: Preview, recording, playback, and network live. backup. playback</p> <p>1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software</p> <p>Remote Control, PTZ, RS485 x 1, 2 USB, 1 IR Controller</p> <p>1 SATA Hard Disk interface Backup: USB2.0 and Net</p> <p>Support remote view by Mobilephone</p>	

LS-9004D

Video Input/Output: BNC 4CH In/ 1CH BNC Out/ 1CH VGA Out
Audio Input/Output: RCA 4CH In/ 1CH Out
Alarm Input/Output: Alarm 4CH In/ 1CH Out
Compression Method: H.264
Real time recording support: CIF:352 240 with 240 Fps (NTSC); 352 288 with 200 Fps (PAL) D1:720 480 with 120 Fps (NTSC); 704 576 with 100 Fps (PAL)
Preview resolution: 720 x 480 ( NTSC ), 704 x 576 ( PAL ) ; Playback resolution: D1 x 4
Hexaplex operation simultaneously: Preview, recording, playback, and network live. backup. playback
1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software
Remote Control, PTZ, RS485 x 1, 2 USB, 1 IR Controller
1 SATA Hard Disk interface Backup: USB2.0 and Network
Support remote view by Mobilephone
Dimensions (L W H): 280mm 229mm 43mm, weight: 3.0kg



LS-9004K

Video Input/Output: BNC 4CH In/ 1CH BNC Out/ 1CH VGA Out
Audio Input/Output: RCA 4CH In/ 1CH Out
Alarm Input/Output: Alarm 4CH In/ 1CH Out
Compression Method: H.264
Real time recording support: CIF:352 240 with 240 Fps (NTSC); 352 288 with 200 Fps (PAL) D1:720 480 with 120 Fps (NTSC); 704 576 with 100 Fps (PAL)
Preview resolution: 720 x 480 ( NTSC ), 704 x 576 ( PAL ) ; Playback resolution: D1 x 4
Hexaplex operation simultaneously: Preview, recording, playback, and network live. backup. playback
1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software
Remote Control, PTZ, RS485 x 1, 2 USB, 1 IR Controller
1 SATA Hard Disk interface Backup: USB2.0 and Network
Support remote view by Mobilephone
Dimensions (L W H): 280mm 229mm 43mm, weight: 3.0kg










LS-9204H

Video Input/Output: BNC 4CH In/1CH BNC Out/ 1CH VGA Out
Audio Input/Output: RCA 4CH In/ 1CH Out
Alarm Input/Output: Alarm 4CH In/ 1CH Out
Compression Method: H.264
Real time recording support: CIF:352 240 with 240 Fps (NTSC); 352 288 with 200 Fps (PAL) D1:720 480 with 120 Fps (NTSC); 704 576 with 100 Fps (PAL)
Preview resolution: 720 x 480 ( NTSC ), 704 x 576 ( PAL ) ; Playback resolution: D1 x 4
Hexaplex operation simultaneously:Preview, recording, playback, and network live. backup. playback
1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software
Remote Control, PTZ, RS485 x 1, 2 USB, 1 IR Controller 2 SATA
Hard Disk interface Backup: USB2.0 and Network
Support remote view by Mobilephone
Dimensions:(L W H) 382mm 258mm 60mm,weight: 3.5kg



## H.264 8CH DVRs

Model No.		Specification	Products Show
LS-9008H		Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out	   
	Audio Input/Output: RCA 8CH In/ 1CH Out		
	Alarm Input/Output: Alarm 4CH In/ 1CH Out		
	Compression Method: H.264		
	Real time recording support: CIF:352 240 with 240 Fps (NTSC); 352 288 with 200 Fps (PAL) D1:720 480 with 60 Fps (NTSC); 704 576 with 50 Fps (PAL)		
	Preview resolution: 720 x 480 ( NTSC ), 704 x 576 ( PAL ) ; Playback resolution: CIF x 8 / D1 x 1		
	Hexaplex operation simultaneously: Preview, recording, playback, and network live. backup. playback		
	1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software		
	Remote Control, PTZ, RS485 x 1, 2 USB, 1 IR Controller		
	1 SATA Hard Disk interface		
	Backup: USB2.0 and Network		
	Support remote view by Mobilephone		
Dimension (L W H): 280mm 229mm 43mm, weight: 4.2kg			

LS-9008S		Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out	  
	Audio Input/Output: RCA 8CH In/ 1CH Out		
	Alarm Input/Output: Alarm 4CH In/ 1CH Out		
	Compression Method: H.264		
	Real time recording support: CIF:352 240 with 240 Fps (NTSC); 352 288 with 200 Fps (PAL) D1:720 480 with 60 Fps (NTSC); 704 576 with 50 Fps (PAL)		
	Preview resolution: 720 x 480 ( NTSC ), 704 x 576 ( PAL ) ; Playback resolution: CIF x 8 / D1 x 1		
	Hexaplex operation simultaneously: Preview, recording, playback, and network live. backup. playback		
	1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software		
	Remote Control, PTZ, RS485 x 1, 2 USB, 1 IR Controller		
	1 SATA Hard Disk interface		
	Backup: USB2.0 and Network		
	Support remote view by Mobilephone		
Dimension (L W H): 280mm 229mm 43mm, weight: 4.2kg			

LS-9008D

Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out

Audio Input/Output: RCA 8CH In/ 1CH Out

Alarm Input/Output: Alarm 4CH In/ 1CH Out

Compression Method: H.264

Real time recording support:  
 CIF:352 240 with 240 Fps (NTSC); 352 288 with 200 Fps (PAL)  
 D1:720 480 with 60 Fps (NTSC); 704 576 with 50 Fps (PAL)

Preview resolution: 720 x 480 ( NTSC ), 704 x 576 ( PAL ) ; Playback resolution: CIF x 8 / D1 x 1

Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback

1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software

Remote Control, PTZ, RS485 x 1, 2 USB, 1 IR Controller

1 SATA Hard Disk interface Backup: USB2.0 and Network

Support remote view by Mobilephone

Dimension (L W H): 280mm 229mm 43mm, weight: 4.2kg



LS-9008K

Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out

Audio Input/Output: RCA 8CH In/ 1CH Out

Alarm Input/Output: Alarm 4CH In/ 1CH Out

Compression Method: H.264

Real time recording support:  
 CIF:352 240 with 240 Fps (NTSC); 352 288 with 200 Fps (PAL)  
 D1:720 480 with 60 Fps (NTSC); 704 576 with 50 Fps (PAL)

Preview resolution: 720 x 480 ( NTSC ), 704 x 576 ( PAL ) ; Playback resolution: CIF x 8 / D1 x 1

Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback

1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software

Remote Control, PTZ, RS485 x 1, 2 USB, 1 IR Controller

1 SATA Hard Disk interface Backup: USB2.0 and Network

Support remote view by Mobilephone

Dimension (L W H): 280mm 229mm 43mm, weight: 4.2kg



LS-9208H

Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out

Audio Input/Output: RCA 8CH In/ 1CH Out

Alarm Input/Output: Alarm 4CH In/ 1CH Out

Compression Method: H.264

Real time recording support:  
 CIF:352 240 with 240 Fps (NTSC); 352 288 with 200 Fps (PAL)  
 D1:720 480 with 60 Fps (NTSC); 704 576 with 50 Fps (PAL)

Preview resolution: 720 x 480 ( NTSC ), 704 x 576 ( PAL ) ; Playback resolution: CIF x 8 / D1 x 1

Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback

1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software

Remote Control, PTZ, RS485 x 1, 2 USB, 1 IR Controller


2 SATA Hard Disk interface Backup: USB2.0 and Network

Support remote view by Mobilephone

Dimensions (L W H): 382mm 258mm 60mm, weight: 5kg



# H.264 16CH DVRs

Model No.	Specification	Products Show
<p><b>LS-9316H</b></p>	<p>Video Input/Output: BNC 16CH In / 2CH Out, VGA 1CH Out, <b>HDMI 1CH Out</b></p>	
	<p>Audio Input/Output: RCA 16CH In/ 1CH Out</p>	
	<p>Alarm Input/Output: Alarm 16CH In/ 1CH Out</p>	
	<p>Compression Method: H.264</p>	
	<p>Real time recording support:            CIF:352 240 with 480 Fps (NTSC); 352 288 with 400 Fps (PAL)            D1:720 480 with 120 Fps (NTSC); 704 576 with 100 Fps (PAL)</p>	
	<p>Preview resolution: 720 x 480 ( NTSC ), 704 x 576 ( PAL );            Playback resolution: CIF x 16 / D1 x 1</p>	
	<p>Hexaplex operation simultaneously: Preview, recording, playback, and network live. backup. playback</p>	
	<p>1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS, Support Internet Explorer and special client software</p>	
	<p>Remote Control, PTZ, RS485x1, <b>RS232x1</b>, 2 USB, 1 IR Controller</p>	
	<p>2 SATA Hard Disk interface Backup: USB2.0 and Network</p>	
	<p>Support remote view by Mobilephone</p>	
	<p>Dimensions (L W H): 405mm 325mm 65mm, weight: 6kg</p>	